

## **MODULAR SERIES**


## **Switched Socket Outlet**

## **PRODUCT SPECIFICATIONS**

## 13A SWITCHED SOCKET OUTLET 13A SWITCHED SOCKET OUTLET WITH NEON INDICATOR







General Data	
Standard Compliance	SLS 734
Warranty	Lifetime
Technical Data	
Key Features	Red indicator gives clear ON indication for Neon socket outlets
	Embossed terminal markings on the rear housing ensures terminal identification and save wiring time
	Internal contact points covered with silver coating enhances the electric strength of the switch
	Safety shutter operated from earth pin ensures that the earth terminal makes the contact first and breaks last, thereby providing maximum safety
	The front plate and back housing made from polycarbonate is of high impact strength and has fire retardant properties
	Easy removal of front plate and frame
	Alignment tolerance of mounting screw holes
	Elegant colours to select, colour combinations possible for outer frames
Power Supply	
Rated Voltage	250V AC
Rated Current	13A
Dimensions	
Steel Plate Size (H*W)	85mm x 84mm
Front Frame Size (H*W)	88mm x 86mm
Terminal Space Capacities	L/N Terminal - 2 x 2.5mm <sup>2</sup> , E Terminal - 2 x 2.5mm <sup>2</sup>
Depth	17mm
Mounting Centers	60.3mm
Compatible Sunk Box	Standard Sunk Box (Depth - 35mm)
Performance Parameters	
Electrical Endurance	15000 cycles (30000 Movements)
Material Overview	
Plastic	Polycarbonate and Nylon-FR grade
Metal	Brass, Phosphor Bronze, Insulated steel plate, Silver on the contact points
Product Colours	Ivory, Platinum, Champagne, Chrome