



## 10A Flush Switches

### PRODUCT SPECIFICATIONS

**1 TO 4 GANG ONE WAY SWITCHES**

**1 TO 4 GANG TWO WAY SWITCHES**

<b>General Data</b>	
Standard Compliance	SLS 1000
Warranty	Lifetime
<b>Technical Data</b>	
Key Features	Front plate is covered with wooden finishing formica layer
	The inner plate and back housing made from polycarbonate is of high impact strength and has fire retardant properties
	Integral rocker switch design with green indicators on switch caps
	Internally looped terminals in multiple gangs to save installation time & cost
	Embossed terminal markings on the rear housing ensures terminal identification and save wiring time
	Internal contact points covered with silver coating enhances the electric strength of the switch
	Alignment tolerance of mounting screw holes
<b>Power Supply</b>	
Rated Voltage	250V AC
Rated Current	10A
<b>Dimensions</b>	
Steel Plate Size (H*W)	86mm x 86mm
Front Face Size (H*W)	86mm x 86mm
Terminal Space Capacity	2 x 1.5mm <sup>2</sup>
Depth	22mm
Mounting Centers	60.3mm
Compatible Sunk Box	Standard Sunk Box (Depth - 35mm)
<b>Performance Parameters</b>	
Electrical Endurance	15000 cycles (30000 Movements)
<b>Material Overview</b>	
Plastic	Polycarbonate and Nylon-FR grade
Metal	Brass, Phosphor Bronze, Insulated steel plate
Product Category	Mahogany, Kumbuk, Teak Finishing